

Alcántara

Decorative finishing paste stucco
with soft suede effect



Perfect Drying Time



Extra Color Selection



Surface Preparation



Smooth Application



1. PRODUCT AND COMPANY INFORMATION

Commercial product name: VENETO-**ALCÁNTARA**

Decorative finish for interiors with a special iridescent effect, soft to the touch and with a silky appearance, perfect for creating classic and modern atmospheres.

Manufacturer:

VENETO COLORS™

www.venetocolors.com

info@venetocolors.com

2. DESCRIPTION

Alcántara is a special breathable plaster which reproduce a final with soft suede effect. Alcántaras available in the following bases: SILVER and GOLD.

The following ready-to-use colors are available for the SILVER base:
RED, VIOLET, WATER, APPLE GREEN, POLAR WHITE.

The ease of application combined with the delicate and refined Alcántara effect make this plaster ideal to give a warm touch to both classic and modern environments.

Alcántara

Decorative finishing paste stucco with soft suede effect

3. FIELD OF APPLICATION

May be applied on surfaces previously painted with Veneto Decofondo, new & old plasters based on hydraulic binders, concrete surfaces, gypsum & gypsum board surfaces, old paints and wall coatings that are organic or mineral in nature, dry, compact, absorbent, and cohesive. Mineral conglomerates of various kinds, as long as they are absorbent. Surfaces should be adequately prepared. Do not apply on freshly painted surfaces. The substrate has to be well prepared and suitable for coating: dry plaster, not any granules from plaster. In the case of old walls make sure there is no poor or dusty paint: remove them if necessary as well as flaking paint. It is recommended the application of 1 coat of Veneto – Acrylic insulating primer, if necessary.

Apply with a brush or roller, one or two coats of DECO PRIMER which has to be thinned up to 5-10 % with water. Allow to dry perfectly, depending on the temperature (from 6 to 12 hours).

Spalter application:

After checking the color chart, add to the base, the quantity of dye necessary to obtain the desired colour. - Sand as necessary using medium or fine grain sandpaper in order to refine any imperfections. Proceed shaving the surface with the coloured plaster ALCÁNTARA, using a stainless steel trowel. - Allow to dry totally and perfectly (from 6 to 12 hours), then refine any imperfections with glass paper.

- Apply the 2nd coat of ALCÁNTARA following the same procedure.
- Clean the trowel with a sponge smoothing the product just applied on the surface.
- Remove the joint material from the trowel with a clean sponge.
- Repeat this operation in order to recreate light and shadow effects, typical of the alcantara fabric. Allow to dry to appreciate the effect.

Roller application:

After checking the color chart, add to the base, the quantity of dye necessary to obtain the desired colour. - Dilute the product with 5-10% of water. Mix carefully until the base is uniformly colored. Apply the colored plaster ALCÁNTARA with a short hair roller over the entire surface. After 10-15 minutes, smooth the surface with a TD spalter. Allow to dry to appreciate the effect from 6 to 12 hours.

Tinting:

The product is available in the following ready to use colours, which can also be used as colour matching bases: silver , aluminium, gold, bronze, copper, slate. The product may be tinted by means of the Tinting System Softwares.

Il colore Italiano

4. TECHNICAL DATA

Nature of the bond	Mineral acrylic plaster, resins in aqueous solution
Viscosity	/
Drying Time	2-6-12h complete
Thinning	Ready to Use
Yield	4-6 m ² /l at 2 coats
Specific weight	1,166kg/lt
Colors	Silver, Gold, Black, Red, Aqua, Violet, Green, Polar White...
Dry aspect	Alcantara fabric
Wet aspect	Liquid mellow
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	30µGr/m ³
TVOC	490µGr/m ³
PH	6-7°C
Cleaning	Water and Soap
Packing	0,750, 2,5lt

CHARACTERISTICS

Characterisic	Breathable
Can be applied on	Walls,Wood
For	Interiors/Exteriors
Certictifications	LOW VOC

TOOLS AND RELATED PRODUCTS

Tools	Stainless Steel Trowel 200x80cm, Stainless Steel Trowel 240x100cm
-------	---

Alcántara

Decorative finishing paste stucco with soft suede effect

5. CLEANING THE TOOLS

All tools must be thoroughly washed using water immediately after use. If the tools are not washed immediately after use, remove the hardened residue mechanically. Removal may be easier if the tools are submerged in water over a period of several hours.

6. HANDLING

No special caution during use is needed when using the product properly. Keep out of reach of children.

7. PERSONAL PROTECTION

Respiratory tract protection: Not needed when the rooms are well aerated. Hands and body protection: When the skin is repeatedly exposed to the mass, a preventative use of protection gloves is recommended. Use long-sleeve work overalls. Eye protection: Use safety goggles as a preventative measure.

8. STORAGE

In accordance with local/regional/European/national regulations It should be stored in a sealed package, cool and dry place and protected from direct sunlight. Temperature between +5°C and +35°C.

9. THEORETICAL CONSUMPTION

Depending on surface smoothness, porosity, and application: 4-6 m²/l at 2 coats. Depending on the desired effect, referred to smooth surfaces with average absorben-
cy. For more info, read the technical data sheet of the product.

10. SAFETY RULES

Limit value EU (Dir. 2004/42/EC)

Cat. A/l: Decorative effect coatings (water-base): 200 g/l
(2010)

ALCÁNTARA Contains max: 200 g/l VOC

Use the product according to current health and safety regulations; after use, do not discard the containers in the environment; allow the residue to dry thoroughly, then treat as special waste. Store out of the reach of children. Do not dispose of residues in the sewers, waterways or ground. For more information consult the safety data sheet.

Il colore Italiano

11. NOTE

Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight. In the original, sealed containers and in appropriate temperature conditions. The period of stability is purely indicative and refers to the minimum stability period of the product if stored under ideal conditions according to the instructions provided. If properly stored the product's stability period may extend several years.

VENETO ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge, however, being elements such as weather conditions, labor, tools, quality of third-party products, and others, not under the direct control of the VENETO, this document does not constitute a warranty, nor does VENETO authorize its agents and/or representatives to provide any kind of warranty based on the information contained in this document. We recommend that you always check the suitability of the product for each specific instance. This supersedes all previous editions.

The company VENETO guarantees that the information contained in this technical data sheet is correct, to the best of its technical and scientific knowledge. Notwithstanding the foregoing, VENETO assumes no responsibility for the results obtained through the use of its product in that the means of application are beyond the scope of its control and/or verification. As such, we recommend checking that each product is suited to the specific case.



VIDEO

Fabbricato da:
VENETO COLORS™

© 2021 Veneto Colors
www.venetocolors.com

