

SAHARA

Sand effect decorative wall paint
with a sand motion effect



Perfect Drying Time



Extra Color Selection



Surface Preparation



Smooth Application



1. PRODUCT AND COMPANY INFORMATION

Commercial product name: **VENETO-SAHARA**
Decorative finishing coat with sand motion effect

Manufacturer:

VENETO COLORS™

www.venetocolors.com

info@venetocolors.com

2. DESCRIPTION

Veneto SAHARA is a decorative finishing coat with special resins, natural fillers and fine glass grains structure, which create a sand motion effect. The product can be used in both classic and modern environments thanks to the numerous base and color variations, satisfying the most demanding requirements and the most refined tastes. Veneto SAHARA is available in the following bases: Oro, Perla, D'argento, Marrone, Bronzo...

Veneto SAHARA can also be requested in the following grain sizes: Fine and Coarse. Veneto SAHARA can be mixed with the special glitter STELLA glitter gold or silver, or the traditional glitter gel - Stardust, for other additional application styles.

Sahara

Sand effect decorative wall paint with a sand motion effect

3. FIELD OF APPLICATION

The surface to be treated must be dry. Conditions and thickness of the plaster layer affect the drying and hardening time, so make sure it has at least 28 days of curing time, depending on temperature.

The substrate has to be well prepared and suitable for coating: dry plaster, not any granules from plaster. In case of old walls make sure there is no poor or dusty paint: remove them if necessary as well as flaking paint.

Apply 1 coat of Transparent acrylic insulating primer insulation if necessary.

Apply with a brush or roller, one or two coats of waterborne primer made up of an emulsion of resins and additives which has to be thinned up to 5-10 % with water.

Allow to dry perfectly, depending on the temperature (from 6 to 12 hours).

After checking the color chart, add to the base, the quantity of dye necessary to obtain the desired colour.

Proceed applying Veneto SAHARA with the SPALTER BRUSH (mm100 or mm70), creating diagonal or alternating effects.

Allow to dry to appreciate the effect.

Depending on the color chosen from the color chart or according to personal taste, a second coat of Veneto SAHARA can be applied.

4. CLEANING THE TOOLS

All tools must be thoroughly washed using water immediately after use. If the tools are not washed immediately after use, remove the hardened residue mechanically. Removal may be easier if the tools are submerged in water over a period of several hours.

5. HANDLING AND STORAGE

No special caution during use is needed when using the product properly. Keep out of reach of children. Store at temperatures between +5 °C and +25 °C, protected from direct sunlight and frost.

6. PERSONAL PROTECTION

Respiratory tract protection: Not needed when the rooms are well aerated. Hands and body protection: When the skin is repeatedly exposed to the mass, a preventative use of protection gloves is recommended. Use long-sleeve work overalls. Eye protection: Use safety goggles as a preventative measure.

Il colore Italiano

7. TECHNICAL DATA

Nature of the bond	Acrylic
Viscosity	/
Drying Time	2 h at touch, 12 h complete
Thinning	Ready to use
Yield	7-8m ² /Lt for FINO; 5-6m ² /Lt for GROSSO
Specific weight	1,127/1,433Kg/Lt
Colors	Oro, Perla, D'argento, Marrone, Bronzo
Dry aspect	Bright decorave finishing coat with sand moon effect
Wet aspect	Liquid metal in grains structure
Storing	Max Temp. +30°C, Min Temp. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	30µGr/m ³
TVOC	490µGr/m ³
PH	7-8°C
Cleaning	Water and Soap
Packing	0.750lt, 2.5lt

CHARACTERISTICS

Characterisic	Washable,Environmentally friendly
Can be applied on	Walls,Wood
For	Interiors/Exteriors
Certictifications	LOW VOC

TOOLS AND RELATED PRODUCTS

Tools	Spalter 100, Spalter 70
-------	-------------------------

* When applying a coat of Veneto SAHARA on primer DECO, any joints could be part of the characteristic of the product. In order to reduce the effect of these joints, apply a second coat, or use Veneto SAHARA on water-based primers

Sahara

Sand effect decorative wall paint with a sand motion effect

8. CLEANING THE TOOLS

All tools must be thoroughly washed using water immediately after use. If the tools are not washed immediately after use, remove the hardened residue mechanically. Removal may be easier if the tools are submerged in water over a period of several hours.

9. PERSONAL PROTECTION

Respiratory tract protection: Not needed when the rooms are well aerated. Hands and body protection: When the skin is repeatedly exposed to the mass, a preventative use of protection gloves is recommended. Use long-sleeve work overalls. Eye protection: Use safety goggles as a preventative measure.

10. SAFETY INFORMATION

The product is free from heavy metals such as lead or chrome. It contains no toxic solvents, aromatics or chlorides. Hazardous polymerisation does not occur. The product is classified as hazardous according to the provisions of Regulation (EC) 1272/2008 (CLP) and subsequent amendments and adjustments. For more information, please refer to the Safety Data Sheet. No special requirements are necessary for storage and handling; the containers, residues, eventual spillages of the material should be cleaned up using absorbent inert material such as sand or soil and then disposed of in accordance with the current regional and national regulations in force. Transportation must be carried out in accordance with international agreements.

11. CAUTION

The raw materials used are natural and may have small differences depending on the batches used. It is therefore recommended to use the same batch of product for each single work to be performed. If this is not possible, mix the batches with each other before use!

Il colore Italiano

12. NOTE

Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight. In the original, sealed containers and in appropriate temperature conditions. The period of stability is purely indicative and refers to the minimum stability period of the product if stored under ideal conditions according to the instructions provided. If properly stored the product's stability period may extend several years.

VENETO ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge, however, being elements such as weather conditions, labor, tools, quality of third-party products, and others, not under the direct control of the VENETO, this document does not constitute a warranty, nor does VENETO authorize its agents and/or representatives to provide any kind of warranty based on the information contained in this document. We recommend that you always check the suitability of the product for each specific instance. This supersedes all previous editions.

The company VENETO guarantees that the information contained in this technical data sheet is correct, to the best of its technical and scientific knowledge. Notwithstanding the foregoing, VENETO assumes no responsibility for the results obtained through the use of its product in that the means of application are beyond the scope of its control and/or verification. As such, we recommend checking that each product is suited to the specific case.



VIDEO

Fabbricato da:
VENETO COLORS™

© 2021 Veneto Colors
www.venetocolors.com



**LOW
VOC**

